



# TAFISUB

technical  
data

## PRODUCT AND COMPANY IDENTIFICATION

### Product Identification

Medium Density Fiberboard (MDF) finished on both ends and lacquered on one side

### Company Information:

TAFISUB

Tableros de Fibras de la Subbetica, SLU

Ctra. Cordoba – Malaga, KM. 74, 700

14900 Lucena (Cordoba)

### Telephone:

957 51 02 86

### RAW MATERIAL INFORMATION

Board: Medium Density Fiberboard certified by the AITIM Stamp

Front: Coated with melamine paper then coated with a patented base primer system then coated with several layers of transparent polyester varnish finished and dried by UV radiation

Back: Coated with melamine paper

Feature	Results	Standard
Chemical Stress	1b	DIN 68861-1
Resistance to cold liquids 1 hr	5	UNE EN 12720:09
Cross cut test	0	UNE EN ISO 240:07
Crack resistance	5	UNE EN 14323:04
Surface soundness	1,5 (0,1)1	UNE EN 311:02
Coldness heat check ( 40 cycles)	Without cracks or superficial defects	AIDIMA
Resistance to light	Blue 8/Grey5	UNE EN 14323:04
Resistance to dry heat 100º C	5	UNE EN 12722:09
Resistance to burn by cigarette	1	UNE EN 14323:04
Resistance to scratching (N)	6,0	UNE EN 14323:04
Resistance to water vapor	4	UNE EN 14323:4
Resistance to impact (Large diameter steel ball)	140	UNE EN 14323:04
Dimensional tolerance	± 0,5 mm	TAFISUB
Bow tolerance	1mm/1m	TAFISUB
Gloss Grade	91 + 5GU	TAFISUB